

# Power It! 7-Outlet Power Strip, 12-ft Cord, Black Housing

MODEL NUMBER: PS712B





### **Highlights**

- 7 outlets
- 12 ft power cord
- · Illuminated on/off switch
- 15 amp circut breaker
- Keyhold mounting slots

#### **Package Includes**

- PS712B Power Strip
- Instruction manual and warranty information

## Description

Tripp Lite's PS712B power strip offers reliable, convenient and cost-effective power distribution for applainces, power tools, lighting and other electrical equipment. PS712B offers 7 total outlets, 12 foot cord. Attractive black housing with keyhole mounting slots and 1 designated transformer plug outlet. Multioutlet strip reduces cable clutter and enables the connection of multiple electrical devices to a single AC wall socket.

PLUG/OUTLETS: Input: NEMA5-15P/Output: 7 NEMA5-15R/12 ft. AC line cord ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA5-15R wall receptacle) FORMAT: Corded multi-outlet strip with 1 transformer spaced outlet

#### **Features**

- 7 outlets / 12-ft cord
- · Attractive black housing
- EMI/RFI noise filtering
- Can accommodate 1 transformer without blocking remaining outlets
- Keyhole supports for wall mounting

## **Specifications**

OVERVIEW	
UPC Code	037332175212
ОИТРИТ	





Frequency Compatibility	50 / 60 Hz
Output (Watts)	1800
Output Receptacles	(7) 5-15R
Circuit Breaker (amps)	15
Transformer Accommodation	(3) Yes
Outlet Orientation	Single row
Right-Angle Outlets	No
INPUT	
Nominal Input Voltage(s) Supported	120V AC
Recommended Electrical Service	120V (110-125V)
Input Cord Gauge Type	14 gauge; SJT
Voltage Compatibility (VAC)	120
Maximum Surge Amps	72000
Input Plug Type	NEMA 5-15P
Input Cord Length (ft.)	12
Input Cord Length (m)	3.66
Integrated Cord Clip	No
- 1	
USER INTERFACE, ALERTS & CON	
USER INTERFACE, ALERTS & CON	TROLS
USER INTERFACE, ALERTS & CON Switches	TROLS
USER INTERFACE, ALERTS & CON Switches  DATALINE SURGE SUPPRESSION	TROLS  Combination AC circuit breaker and 2 position red illuminated on/off power switch
USER INTERFACE, ALERTS & CON Switches  DATALINE SURGE SUPPRESSION Cable (Coax) Protection	TROLS  Combination AC circuit breaker and 2 position red illuminated on/off power switch  No
USER INTERFACE, ALERTS & CON Switches  DATALINE SURGE SUPPRESSION Cable (Coax) Protection	TROLS  Combination AC circuit breaker and 2 position red illuminated on/off power switch  No
USER INTERFACE, ALERTS & CON Switches  DATALINE SURGE SUPPRESSION Cable (Coax) Protection Network (Ethernet) Protection	TROLS  Combination AC circuit breaker and 2 position red illuminated on/off power switch  No
USER INTERFACE, ALERTS & CON Switches  DATALINE SURGE SUPPRESSION Cable (Coax) Protection Network (Ethernet) Protection  PHYSICAL	TROLS  Combination AC circuit breaker and 2 position red illuminated on/off power switch  No No
USER INTERFACE, ALERTS & CON Switches  DATALINE SURGE SUPPRESSION Cable (Coax) Protection Network (Ethernet) Protection  PHYSICAL Shipping Dimensions (hwd / in.)	Combination AC circuit breaker and 2 position red illuminated on/off power switch  No No 2.50 x 4.90 x 13.80
USER INTERFACE, ALERTS & CON Switches  DATALINE SURGE SUPPRESSION Cable (Coax) Protection Network (Ethernet) Protection  PHYSICAL Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm)	TROLS  Combination AC circuit breaker and 2 position red illuminated on/off power switch  No  No  2.50 x 4.90 x 13.80  6.35 x 12.45 x 35.05
USER INTERFACE, ALERTS & CON Switches  DATALINE SURGE SUPPRESSION  Cable (Coax) Protection  Network (Ethernet) Protection  PHYSICAL  Shipping Dimensions (hwd / in.)  Shipping Dimensions (hwd / cm)  Shipping Weight (lbs.)	TROLS  Combination AC circuit breaker and 2 position red illuminated on/off power switch  No No  2.50 x 4.90 x 13.80  6.35 x 12.45 x 35.05  1.90
USER INTERFACE, ALERTS & CON Switches  DATALINE SURGE SUPPRESSION Cable (Coax) Protection  Network (Ethernet) Protection  PHYSICAL Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) Shipping Weight (lbs.) Shipping Weight (kg)	TROLS  Combination AC circuit breaker and 2 position red illuminated on/off power switch  No No  2.50 x 4.90 x 13.80  6.35 x 12.45 x 35.05  1.90  0.86
USER INTERFACE, ALERTS & CON Switches  DATALINE SURGE SUPPRESSION Cable (Coax) Protection  Network (Ethernet) Protection  PHYSICAL Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) Shipping Weight (lbs.) Shipping Weight (kg) Unit Dimensions (hwd / in.)	Combination AC circuit breaker and 2 position red illuminated on/off power switch     No
USER INTERFACE, ALERTS & CON Switches  DATALINE SURGE SUPPRESSION Cable (Coax) Protection  Network (Ethernet) Protection  PHYSICAL Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) Shipping Weight (lbs.) Shipping Weight (kg) Unit Dimensions (hwd / in.) Unit Dimensions (hwd / cm)	TROLS  Combination AC circuit breaker and 2 position red illuminated on/off power switch  No  No  No  2.50 x 4.90 x 13.80  6.35 x 12.45 x 35.05  1.90  0.86  1.32 x 2.05 x 11.69  3.35 x 5.21 x 29.69
USER INTERFACE, ALERTS & CON Switches  DATALINE SURGE SUPPRESSION Cable (Coax) Protection Network (Ethernet) Protection  PHYSICAL Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) Shipping Weight (lbs.) Shipping Weight (kg) Unit Dimensions (hwd / in.) Unit Dimensions (hwd / cm) Unit Weight (lbs.)	TROLS  Combination AC circuit breaker and 2 position red illuminated on/off power switch  No  No  2.50 x 4.90 x 13.80  6.35 x 12.45 x 35.05  1.90  0.86  1.32 x 2.05 x 11.69  3.35 x 5.21 x 29.69  1.76





Receptacle Color	Black	
Color (AC Line Cord)	Black	
Color	Black	
Outlets Measurement (Center to Center)	Distance between standard outlets = 29mm; Distance between last standard outlet and transformer outlet = 33mm	
Keyhole Slot Mounting Measurement (Center to Center)	Distance between slots = 151mm; Distance between slot height = 24mm	
Anti-Microbial Protected	No	
CERTIFICATIONS		
Additional International Approvals	RoHS	
NOM (Mexico)	NOM	
UL1363 (Power Tap)	UL1363	
Canada	cUL	
Approvals	Exceeds IEEE 587 category A&B specifications	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>