

# Nickel Plated Brass Liquid Tight Strain Relief Fittings

## EMI/RFI Proof - PG/NPT/Metric & Elongated



### EMI/RFI Ground Proof: Standard Version (-BE)

Part Numbers				Cable Range	Thread Type & Size	Dimensions in Inches (mm)					
- 40 °F to 212 °F (- 40 °C to 100 °C)						A	B	C	D	D	F <sub>T</sub> /F
Dome Standard	Flex Standard	Dome Elongated	Flex Elongated	Inches (mm)	Clearance Hole + .01" (+.25 mm)	Body Length (Dome)	Body Length (Flex)	Thread Length Standard	Thread Length Elongated	Wrench Flats	
CD07AA-BE	CF07AA-BE	CD07CA-BE	CF07CA-BE	.12 - .26 (3 - 6.5)	PG 7 / 1/4" NPT	.49 (12.5)	.75 (19)	2.17 (55)	.20 (5)	.39 (10)	.55 (14)
CD07AR-BE	CF07AR-BE	CD07CR-BE	CF07CR-BE	.08 - .20 (2 - 5)							
CD09AA-BE	CF09AA-BE	CD09CA-BE	CF09CA-BE	.16 - .31 (4 - 8)	PG 9	.60 (15.2)	.83 (21)	2.60 (66)	.24 (6)	.39 (10)	.67 (17)
CD09AR-BE	CF09AR-BE	CD09CR-BE	CF09CR-BE	.08 - .24 (2 - 6)							
CD11AA-BE	CF11AA-BE	CD11CA-BE	CF11CA-BE	.20 - .39 (5 - 10)	PG 11	.73 (18.5)	.87 (22)	3.03 (77)	.24 (6)	.39 (10)	.79 (20)
CD11AR-BE	CF11AR-BE	CD11CR-BE	CF11CR-BE	.12 - .28 (3 - 7)							
CD13AA-BE	CF13AA-BE	CD13CA-BE	CF13CA-BE	.24 - .47 (6 - 12)	PG 13 / 13.5	.80 (20.3)	.94 (24)	3.46 (88)	.26 (6.5)	.39 (10)	.87 (22)
CD13AR-BE	CF13AR-BE	CD13CR-BE	CF13CR-BE	.20 - .35 (5 - 9)							
CD16AA-BE	CF16AA-BE	CD16CA-BE	CF16CA-BE	.39 - .55 (10 - 14)	PG 16	.89 (22.5)	.91 (23)	3.86 (98)	.26 (6.5)	.39 (10)	.94 (24)
CD16AR-BE	CF16AR-BE	CD16CR-BE	CF16CR-BE	.28 - .47 (7 - 12)							
CD21AA-BE	CF21AA-BE	CD21CA-BE	CF21CA-BE	.51 - .71 (13 - 18)	PG 21	1.12 (28.4)	.94 (24)	4.37 (111)	.28 (7)	.47 (12)	1.18 (30)
CD21AR-BE	CF21AR-BE	CD21CR-BE	CF21CR-BE	.35 - .63 (9 - 16)							
CD29AA-BE	-	CD29CA-BE	-	.71 - .98 (18 - 25)	PG 29	1.47 (37.3)	1.14 (29)	-	.31 (8)	.47 (12)	1.57 (40)
CD29AR-BE	-	CD29CR-BE	-	.51 - .79 (13 - 20)							
CD36AA-BE	-	CD36CA-BE	-	.87 - 1.26 (22 - 32)	PG 36	1.85 (47)	1.38 (35)	-	.31 (8)	.59 (15)	1.97 (50)
CD36AR-BE	-	CD36CR-BE	-	.79 - 1.02 (20 - 26)							
CD42AA-BE	-	CD42CA-BE	-	1.26 - 1.50 (32 - 38)	PG 42	2.13 (54.1)	1.46 (37)	-	.35 (9)	.59 (15)	2.24 (57)
CD42AR-BE	-	CD42CR-BE	-	.98 - 1.22 (25 - 31)							
CD48AA-BE	-	CD48CA-BE	-	1.46 - 1.73 (37 - 44)	PG 48	2.34 (59.4)	1.50 (38)	-	.39 (10)	.59 (15)	2.52 (64)
CD48AR-BE	-	CD48CR-BE	-	1.14 - 1.38 (29 - 35)							
CD09NA-BE	CF09NA-BE	-	-	.16 - .31 (4 - 8)	3/8" NPT	.68 (17.2)	.83 (21)	2.60 (66)	.59 (15)	-	.67 (17) / .75 (19)
CD09NR-BE	CF09NR-BE	-	-	.08 - .24 (2 - 6)							
CD13NA-BE	CF13NA-BE	-	-	.24 - .47 (6 - 12)	1/2" NPT	.83 (21.1)	.94 (24)	3.46 (88)	.51 (13)	-	.87 (22) / .94 (24)
CD13NR-BE	CF13NR-BE	-	-	.20 - .35 (5 - 9)							
CD21NA-BE	CF21NA-BE	-	-	.51 - .71 (13 - 18)	3/4" NPT	1.05 (26.7)	.98 (25)	4.37 (111)	.51 (13)	-	1.18 (30)
CD21NR-BE	CF21NR-BE	-	-	.35 - .63 (9 - 16)							
CD12MA-BE	CF12MA-BE	CD12DA-BE	CF12DA-BE	.12 - .26 (3 - 6.5)	M12 x 1.5	.47 (12)	.75 (19)	2.17 (55)	.26 (6.5)	.39 (10)	.55 (14)
CD12MR-BE	CF12MR-BE	CD12DR-BE	CF12DR-BE	.08 - .20 (2 - 5)							
CD16MA-BE	CF16MA-BE	CD16DA-BE	CF16DA-BE	.20 - .39 (5 - 10)	M16 x 1.5	.63 (16)	.87 (22)	3.03 (77)	.24 (6)	.39 (10)	.79 (20)
CD16MR-BE	CF16MR-BE	CD16DR-BE	CF16DR-BE	.12 - .28 (3 - 7)							
CD20MA-BE	CF20MA-BE	CD20DA-BE	CF20DA-BE	.39 - .55 (10 - 14)	M20 x 1.5	.79 (20)	.94 (24)	3.86 (98)	.24 (6)	.39 (10)	.94 (24)
CD20MR-BE	CF20MR-BE	CD20DR-BE	CF20DR-BE	.28 - .47 (7 - 12)							
CD25MA-BE	CF25MA-BE	CD25DA-BE	CF25DA-BE	.51 - .71 (13 - 18)	M25 x 1.5	.98 (25)	1.02 (26)	4.37 (111)	.28 (7)	.47 (12)	1.18 (30)
CD25MR-BE	CF25MR-BE	CD25DR-BE	CF25DR-BE	.35 - .63 (9 - 16)							
CD32MA-BE	-	CD32DA-BE	-	.71 - .98 (18 - 25)	M32 x 1.5	1.26 (32)	1.22 (31)	-	.31 (8)	.47 (12)	1.57 (40)
CD32MR-BE	-	CD32DR-BE	-	.51 - .79 (13 - 20)							
CD40MA-BE	-	CD40DA-BE	-	.87 - 1.26 (22 - 32)	M40 x 1.5	1.57 (40)	1.46 (37)	-	.31 (8)	.59 (15)	1.97 (50)
CD40MR-BE	-	CD40DR-BE	-	.79 - 1.02 (20 - 26)							
CD50MA-BE	-	Available	-	1.26 - 1.50 (32 - 38)	M50 x 1.5	1.97 (50)	1.46 (37)	-	.35 (9)	.59 (15)	2.24 (57)
CD50MR-BE	-	Available	-	.98 - 1.22 (25 - 31)							
CD63MA-BE	-	Available	-	1.46 - 1.73 (37 - 44)	M63 x 1.5	2.48 (63)	1.50 (38)	-	.39 (10)	.59 (15)	2.52 (64) / 2.68 (68)
CD63MR-BE	-	Available	-	1.14 - 1.38 (29 - 35)							

\*Note: VDE Approval only applies to Dome Fittings with Metric Threads. UL, UR & CSA Approval applies to Dome Fittings.



Standard (-BE)

EMI/RFI Fittings are also available with High Performance Clamp or in Stainless Steel. For inquiries - please call our Inside Technical Sales Department (800-456-9012 or 303-699-1135).

Dome Fittings also available with the following approvals:



www.sealconex.com

