

# Nickel Plated Brass Liquid Tight Strain Relief Fittings Multi-Hole - PG Threads



| Part Numbers                          |           | Thread Type & Size           | Dimensions in Inches (mm) |                   |               |                              |
|---------------------------------------|-----------|------------------------------|---------------------------|-------------------|---------------|------------------------------|
| - 40 °F to 212 °F (- 40 °C to 100 °C) |           |                              | No. of Holes              | Diameter of Holes |               | Part Numbers of Inserts only |
| Dome                                  | Flex **   | See page 49 for thread specs | mm                        | Inches            |               |                              |
| CD07AP-BR                             | CF07AP-BR |                              | PG 7 / 1/4" NPT           | Solid Insert      |               | 1.089.0799.19                |
| CD09A1-BR                             | CF09A1-BR | PG 9                         | 4                         | 1.4               | .06           | 1.089.0900.19                |
| CD09A2-BR                             | CF09A2-BR |                              | 2                         | 3.0               | .12           | 1.089.0901.19                |
| CD09A3-BR                             | CF09A3-BR |                              | 5                         | 1.6               | .06           | 1.089.0902.19                |
| CD09A4-BR                             | CF09A4-BR |                              | 2                         | 1.7               | .07           | 1.089.0903.19                |
| CD09A5-BR                             | CF09A5-BR |                              | 10                        | 1.4               | .06           | 1.089.0904.19                |
| CD09A6-BR                             | CF09A6-BR |                              | 6                         | 1.4               | .06           | 1.089.0905.19                |
| CD09A7-BR                             | CF09A7-BR |                              | 3                         | 1.7               | .07           | 1.089.0906.19                |
| CD09A8-BR                             | CF09A8-BR |                              | 4                         | 1.7               | .07           | 1.089.0907.19                |
| CD09A9-BR                             | CF09A9-BR |                              | 4                         | 2.3               | .09           | 1.089.0908.19                |
| CD09AP-BR                             | CF09AP-BR |                              | Solid Insert              |                   | 1.089.0999.19 |                              |
| CD11A1-BR                             | CF11A1-BR | PG 11                        | 2                         | 3.0               | .12           | 1.089.1100.19                |
| CD11A2-BR                             | CF11A2-BR |                              | 3                         | 3.0               | .12           | 1.089.1101.19                |
| CD11A3-BR                             | CF11A3-BR |                              | 2                         | 4.0               | .16           | 1.089.1102.19                |
| CD11A4-BR                             | CF11A4-BR |                              | 3                         | 1.5               | .06           | 1.089.1103.19                |
| CD11A5-BR                             | CF11A5-BR |                              | 4                         | 2.8               | .11           | 1.089.1104.19                |
| CD11AP-BR                             | CF11AP-BR | Solid Insert                 |                           | 1.089.1199.19     |               |                              |
| CD13A1-BR                             | CF13A1-BR | PG 13 / 13.5                 | 3                         | 2.0               | .08           | 1.089.1300.19                |
| CD13A2-BR                             | CF13A2-BR |                              | 6                         | 3.0               | .12           | 1.089.1301.19                |
| CD13A3-BR                             | CF13A3-BR |                              | 3                         | 4.0               | .16           | 1.089.1302.19                |
| CD13A4-BR                             | CF13A4-BR |                              | 2                         | 5.0               | .20           | 1.089.1303.19                |
| CD13A5-BR                             | CF13A5-BR |                              | 3                         | 3.0               | .12           | 1.089.1304.19                |
| CD13A6-BR                             | CF13A6-BR |                              | 2                         | 5.2               | .20           | 1.089.1305.19                |
| CD13A7-BR                             | CF13A7-BR |                              | 2                         | 3.8               | .15           | 1.089.1306.19                |
| CD13A8-BR                             | CF13A8-BR |                              | 2                         | 4.2               | .17           | 1.089.1307.19                |
| CD13A9-BR                             | CF13A9-BR |                              | 2                         | 2.5               | .10           | 1.089.1308.19                |
| CD13AP-BR                             | CF13AP-BR |                              | Solid Insert              |                   | 1.089.1399.19 |                              |
| CD16A1-BR                             | CF16A1-BR | PG 16                        | 3                         | 3.0               | .12           | 1.089.1600.19                |
| CD16A2-BR                             | CF16A2-BR |                              | 3                         | 4.0               | .16           | 1.089.1601.19                |
| CD16A3-BR                             | CF16A3-BR |                              | 4                         | 4.0               | .16           | 1.089.1602.19                |
| CD16A4-BR                             | CF16A4-BR |                              | 5                         | 4.0               | .16           | 1.089.1603.19                |
| CD16A5-BR                             | CF16A5-BR |                              | 6                         | 4.0               | .16           | 1.089.1604.19                |
| CD16A6-BR                             | CF16A6-BR |                              | 2                         | 6.0               | .24           | 1.089.1605.19                |
| CD16A7-BR                             | CF16A7-BR |                              | 3                         | 5.6               | .22           | 1.089.1606.19                |
| CD16A8-BR                             | CF16A8-BR |                              | 6                         | 3.0               | .12           | 1.089.1607.19                |
| CD16A9-BR                             | CF16A9-BR |                              | *4                        | 3.0               | .12           | *1.089.1610.19               |
| CD16A0-BR                             | CF16A0-BR |                              | 6                         | 3.8               | .15           | 1.089.1609.19                |
| CD16AP-BR                             | CF16AP-BR | Solid Insert                 |                           | 1.089.1699.19     |               |                              |

\*Note: This Insert has slotted holes.

\*\*Note: Flex Fittings are not a standard item, assembly required.

\*Note: CSA and CE Approvals only applies to Dome Fittings.



Multi-Hole Inserts are available in Silicone and FPM on request.

| Part Numbers                          |           | Thread Type & Size           | Dimensions in Inches (mm) |                   |               |                              |               |
|---------------------------------------|-----------|------------------------------|---------------------------|-------------------|---------------|------------------------------|---------------|
| - 40 °F to 212 °F (- 40 °C to 100 °C) |           |                              | No. of Holes              | Diameter of Holes |               | Part Numbers of Inserts only |               |
| Dome                                  | Flex **   | See page 49 for thread specs | mm                        | Inches            |               |                              |               |
| CD21A1-BR                             | CF21A1-BR |                              | PG 21                     | 4                 | 6.0           | .24                          | 1.089.2100.19 |
| CD21A2-BR                             | CF21A2-BR | 3                            |                           | 7.0               | .28           | 1.089.2101.19                |               |
| CD21A3-BR                             | CF21A3-BR | 2                            |                           | 8.0               | .31           | 1.089.2102.19                |               |
| CD21A4-BR                             | CF21A4-BR | 4                            |                           | 5.0               | .20           | 1.089.2103.19                |               |
| CD21A5-BR                             | CF21A5-BR | 1                            |                           | 8.0               | .31           | 1.089.2104.19                |               |
| CD21A6-BR                             | CF21A6-BR | 4                            |                           | 5.2               | .20           | 1.089.2105.19                |               |
| CD21A7-BR                             | CF21A7-BR | 3                            |                           | 5.2               | .20           | 1.089.2106.19                |               |
| CD21A8-BR                             | CF21A8-BR | 4/1                          |                           | 5.2 / 3.7         | .20 / .15     | 1.089.2107.19                |               |
| CD21A9-BR                             | CF21A9-BR | 2                            |                           | 7.4               | .29           | 1.089.2108.19                |               |
| CD21AP-BR                             | CF21AP-BR | Solid Insert                 |                           | 1.089.2199.19     |               |                              |               |
| CD29A1-BR                             | -         | PG 29                        |                           | 6                 | 6.5           | .26                          | 1.089.2900.19 |
| CD29A2-BR                             | -         |                              |                           | 4                 | 9.0           | .35                          | 1.089.2901.19 |
| CD29A3-BR                             | -         |                              |                           | 4                 | 9.5           | .37                          | 1.089.2902.19 |
| CD29A9-BR                             | -         |                              |                           | 2                 | 11            | .43                          | 1.089.2908.19 |
| CD29AP-BR                             | -         |                              |                           | Solid Insert      |               | 1.089.2999.19                |               |
| CD36A1-BR                             | -         | PG 36                        | 5                         | 9.0               | .35           | 1.089.3600.19                |               |
| CD36A2-BR                             | -         |                              | 7                         | 9.0               | .35           | 1.089.3601.19                |               |
| CD36A3-BR                             | -         |                              | 6                         | 8.0               | .31           | 1.089.3602.19                |               |
| CD36A4-BR                             | -         |                              | 2                         | 15.0              | .59           | 1.089.3603.19                |               |
| CD36AP-BR                             | -         |                              | Solid Insert              |                   | 1.089.3699.19 |                              |               |
| CD42A1-BR                             | -         | PG 42                        | 3                         | 14.0              | .55           | 1.089.4203.19                |               |
| CD42AP-BR                             | -         |                              | Solid Insert              |                   | 1.089.4299.19 |                              |               |
| CD48A1-BR                             | -         | PG 48                        | 8                         | 10.0              | .39           | 1.089.4800.19                |               |
| CD48A2-BR                             | -         |                              | 6                         | 12.0              | .47           | 1.089.4801.19                |               |
| CD48A3-BR                             | -         |                              | 3                         | 18.0              | .71           | 1.089.4802.19                |               |
| CD48AP-BR                             | -         |                              | Solid Insert              |                   | 1.089.4899.19 |                              |               |

For Strain Relief Fitting specifications and dimensions see Page 14.



Solid Plug can be customized!

Dome Fittings also available with the following approvals:



Optional Locking Nuts & Other Accessories starting on Page 28 - 39.

