






Stainless Steel Strain Relief Fittings can be used in many applications, where the environment dictates a corrosion proof solution.

Typical Application:

- Off-shore
- Marine
- Chemical Plants
- Food Processing
- Clean Room
- Other Rugged Applications





(303) INOX Stainless Steel also available in **NPT Threads** upon request.





303 / 316L Stainless Steel: Outer High Performance, High/Low Temp. & Corrosion Resistant

PVDF / Stainless Steel

Part Numbers		Cable Range Inches (mm)	Thread Type & Size See page 56 for thread specs	Dimensions in Inches (mm)			
-40°F to 212°F (-40°C to 100°C)	-31°F to 302°F (-35°C to 150°C)			A Clearance Hole +.01" (+.25 mm)	B Body Length	TL Thread Length	F ₁ /F Wrench Flats
							
Standard w/ Buna-N Insert	PVDF w/ FKM Insert						
CD07AA-SS	CD07AA-SV	.12 - .26 (3 - 6.5)	PG 7	.49 (12.5)	.75 (19)	.20 (5)	.55 (14)
CD07AR-SS	CD07AR-SV	.08 - .20 (2 - 5)					
CD09AA-SS	CD09AA-SV	.16 - .31 (4 - 8)	PG 9	.60 (15.2)	.83 (21)	.24 (6)	.67 (17)
CD09AR-SS	CD09AR-SV	.08 - .24 (2 - 6)					
CD11AA-SS	CD11AA-SV	.20 - .39 (5 - 10)	PG 11	.73 (18.5)	.87 (22)	.24 (6)	.87 (22)
CD11AR-SS	CD11AR-SV	.12 - .28 (3 - 7)					
CD13AA-SS	CD13AA-SV	.24 - .47 (6 - 12)	PG 13 / 13.5	.80 (20.3)	.94 (24)	.26 (6.5)	.87 (22)
CD13AR-SS	CD13AR-SV	.20 - .35 (5 - 9)					
CD16AA-SS	CD16AA-SV	.39 - .55 (10 - 14)	PG 16	.89 (22.5)	.91 (23)	.26 (6.5)	.94 (24)
CD16AR-SS	CD16AR-SV	.28 - .47 (7-12)					
CD21AA-SS	CD21AA-SV	.51 - .71 (13 - 18)	PG 21	1.12 (28.4)	.94 (24)	.28 (7)	1.18 (30)
CD21AR-SS	CD21AR-SV	.35 - .63 (9 - 16)					
CD29AA-SS	CD29AA-SV	.71 - .98 (18 - 25)	PG 29	1.47 (37.3)	1.14 (29)	.31 (8)	1.61 (41)
CD29AR-SS	CD29AR-SV	.51 - .79 (13 - 20)					
CD36AA-SS	CD36AA-SV	.87 - 1.26 (22 - 32)	PG 36	1.85 (47)	1.38 (35)	.31 (8)	1.97 (50)
CD36AR-SS	CD36AR-SV	.79 - 1.02 (20 - 26)					
CD42AA-SS	CD42AA-SV	1.26 - 1.50 (32 - 38)	PG 42	2.13 (54.1)	1.46 (37)	.35 (9)	2.24 (57)
CD42AR-SS	CD42AR-SV	.98 - 1.22 (25 - 31)					
CD48AA-SS	CD48AA-SV	1.46 - 1.73 (37 - 44)	PG 48	2.34 (59.4)	1.50 (38)	.39 (10)	2.52 (64)
CD48AR-SS	CD48AR-SV	1.14 - 1.38 (29 - 35)					
CD12MA-SS	CD12MA-SV	.12 - .26 (3 - 6.5)	M12 X 1.5	.47 (12)	.75 (19)	.26 (6.5)	.55 (14)
CD12MR-SS	CD12MR-SV	.08 - .20 (2 - 5)					
CD16MA-SS	CD16MA-SV	.20 - .39 (5 - 10)	M16 X 1.5	.63 (16)	.87 (22)	.24 (6)	.87 (22)
CD16MR-SS	CD16MR-SV	.12 - .28 (3 - 7)					
CD20MA-SS	CD20MA-SV	.39 - .55 (10 - 14)	M20 X 1.5	.79 (20)	.91 (23)	.24 (6)	.94 (24)
CD20MR-SS	CD20MR-SV	.28 - .47 (7-12)					
CD25MA-SS	CD25MA-SV	.51 - .71 (13 - 18)	M25 X 1.5	.98 (25)	.94 (24)	.28 (7)	1.18 (30)
CD25MR-SS	CD25MR-SV	.35 - .63 (9 - 16)					
CD32MA-SS	CD32MA-SV	.71 - .98 (18 - 25)	M32 X 1.5	1.26 (32)	1.22 (31)	.31 (8)	1.61 (47)
CD32MR-SS	CD32MR-SV	.51 - .79 (13 - 20)					
CD40MA-SS	CD40MA-SV	.87 - 1.26 (22 - 32)	M40 X 1.5	1.57 (40)	1.46 (37)	.31 (8)	1.97 (50)
CD40MR-SS	CD40MR-SV	.79 - 1.02 (20 - 26)					
CD50MA-SS	-	1.26 - 1.50 (32 - 38)	M50 X 1.5	1.97 (50)	1.46 (37)	.35 (9)	2.36 (60)
CD50MR-SS	-	.98 - 1.22 (25 - 31)					
CD63MA-SS	-	1.46 - 1.73 (37 - 44)	M63 X 1.5	2.48 (63)	1.50 (38)	.39 (10)	2.52 (64) / 2.68 (68)
CD63MR-SS	-	1.14 - 1.38 (29 - 35)					

*Note: CSA and CE Approvals only applies to Standard Fittings.

*Note: VDE Approval only applies to Dome Fittings with Metric Threads.

Part Numbers		Cable Range Inches (mm)	Thread Type & Size See page 56 for thread specs	Dimensions in Inches (mm)			
-40°F to 212°F (-40°C to 100°C)	-31°F to 302°F (-35°C to 150°C)			A Clearance Hole +.01" (+.25 mm)	B Body Length	TL Thread Length	F ₁ /F Wrench Flats
							
Standard w/ Buna-N Insert	PVDF w/ FKM Insert						
CD09NA-6S	CD09NA-6V	.16 - .31 (4 - 8)	3/8" NPT	.68 (17.2)	.83 (21)	.59 (15)	.67 (17) / .75 (19)
CD09NR-6S	CD09NR-6V	.08 - .24 (2 - 6)					
CD13NA-6S	CD13NA-6V	.24 - .47 (6 - 12)	1/2" NPT	.83 (21.1)	.94 (24)	.51 (13)	.87 (22) / .94 (24)
CD13NR-6S	CD13NR-6V	.20 - .35 (5 - 9)					
CD21NA-6S	CD21NA-6V	.51 - .71 (13 - 18)	3/4" NPT	1.05 (26.7)	.98 (25)	.51 (13)	1.18 (30)
CD21NR-6S	CD21NR-6V	.35 - .63 (9 - 16)					
CD29NA-6S	CD29NA-6V	.71 - .98 (18 - 25)	1" NPT	1.35 (34.3)	1.14 (29)	.75 (19)	1.61 (41)
CD29NR-6S	CD29NR-6V	.51 - .79 (13 - 20)					

The 316L material is much harder and ideal for direct exposure to salt water and chemical solutions in marine, off-shore, pharmaceutical, etc.

(316L) INOX Stainless Steel also available in **PG and Metric Threads** upon request.

Dome Fittings also available with the following approvals:



www.SealconEX.com



Optional Locking Nuts, O-Rings & Other Accessories starting on Page 29 - 40.